

HAIKU
BAXTER P.



Struttura, basamento e dettagli in nickel spazzolato semi-opaco. Paralume in vetro soffiato temperato grigio acciaio, con sfumatura: trasparente; sfumato; incamiciato bianco e incamiciato bianco a fasce. Lampada con fonte luminosa a led.

Possibile dimmerazione previa richiesta all'ufficio tecnico e conseguente preventivo.

Cassa in legno dotata di due sensori per verifica di eventuali danni durante il trasporto. (Fare riferimento a "Avvertenze importanti").

Frame, base and details in semi-matte brushed nickel. Lampshade in tempered blown glass steel gray with shades of smooth transparent steel gray, shaded steel gray, gray jacketed steel gray and white jacketed with smooth steel gray bands. Lamp with led light source.


Dimming is possible subject to request to the technical department and consequent quotation.

Wooden crate equipped with two sensors to check for any damage during transport. (Refer to "Important information").

Ø30 h63

Lampada da tavolo C. C table lamp.


Striscia LED 3000K - 19,2W/MT - alimentatore 110/240 V - 24V. Classe 2, IP20. 3200 lumen.
3000K LED strip - 19,2 W/MT - 110/240V power supply - 24V. Class 2, IP20. 3200 lumens.



Ø40 h128

Lampada da terra. Floor lamp.


Striscia LED 3000K - 19,2W/MT - alimentatore 110/240 V - 24V. Classe 1, IP20. 7500 lumen.
3000K LED strip - 19,2 W/MT - 110/240V power supply - 24V. Class 1, IP20. 7500 lumens.



Ø30 h58

Sospensione A. A hanging lamp.

Striscia LED 3000K - 19,2W/MT - alimentatore 110/240 V - 24V. Classe 1, IP20. 4350 lumen.
3000K LED strip - 19,2 W/MT - 110/240V power supply - 24V. Class 1, IP20. 4350 lumens.



Ø30 h93

Sospensione B. B hanging lamp.

Striscia LED 3000K - 19,2W/MT - alimentatore 110/240 V - 24V. Classe 1, IP20. 6550 lumen.
3000K LED strip - 19,2 W/MT - 110/240V power supply - 24V. Class 1, IP20. 6550 lumens.

