



Paralume in metacrilato curvato stampato spessore 8 mm. Profilati e dettagli in metallo ottonato satinato con vernice opaca. Lampada con fonte luminosa a led 2700°K.

Applique 80: Striscia LED 2700K – 20 W/MT. Alimentatore 110/240 V – 24V. 1920 lumen.

Applique 150: Striscia LED 2700K – 20 W/MT. Alimentatore 110/240 V – 24V. 3600 lumen.

Sospensione a "U" 150: Strip led inferiore: Striscia LED 2700K – 14W/MT. Alimentatore 110/240V – 24V. 2250 lumen.

Strip led superiore che eccita metacrilato: Striscia LED 2700K – 20W/MT. Alimentatore 110/240V – 24V. 3600 lumen.

8 mm thick lampshade in printed curved methacrylate. Profiles and details in satin brass-coated metal with matte varnish. Lamp with 2700K led light source.

Applique 80: 2700K LED strip – 20W/MT. 110/240V – 24V ballast. 1920 lumens.


Applique 150: 2700K LED strip – 20W/MT. 110/240V – 24V ballast. 3600 lumen.

"U" Hanging lamp 150: Lower led-strip: 2700K LED strip – 14W/MT. 110/240V – 24V ballast. 2250 lumens.

Upper led-strip that energizes Methacrylate: 2700K LED strip – 20W/MT. 110/240V – 24V ballast. 3600 lumens.


14 x 12 h80 | 0,04 m³

Applique.



26 x 20 h150 | 0,19 m³

Applique.



150 x 33 h36 | 0,36 m³

Sospensione. Hanging lamp.

